

BLACK GOLD
GASOLINE / CNG/ LPG ENGINE OIL
SYNTHETIC BLEND GX9
API SN/CF SAE 10W-40

DESCRIPTION:

BLACK GOLD GASOLINE ENGINE OIL GX9 is an advance carefully balanced synthetic blend gasoline engine lubricant formulated with specially designed additive package and highly refined base oils for naturally aspirated or turbo charge vehicles requiring API SN performance lubricants.

APPLICATIONS:

BLACK GOLD GASOLINE ENGINE OIL GX9 is recommended for naturally aspirated, turbocharged gasoline engines. Also suitable for Passenger cars, Vans, Light commercial vehicles engines where API SN or CF performance is recommended. It is equally suitable for engines converted to **CNG** or **LPG**. **BLACK GOLD GASOLINE ENGINE OIL GX9** is also capable of meeting API specification **SL, SJ, SG, SF** and **API CF**

BENEFITS:

- Excellent resistibility to high temperature degradation
- Superior protection against varnish, corrosion, and sludge formation
- Prolongs engine life
- Stay in grade characteristics at high temperature
- Having effective shared stability and anti-oxidant characteristics

TYPICAL DATA		
Product	BLACK GOLD GASOLINE ENGINE OIL GX9	
SAE Rating	SAE 10W-40	
API Level	SN/ CF	
Physical Characteristics	Test Method	Typical Value
SAE Rating		10W-40
Kinematic Viscosity @ 100 °C (cst)	ASTM D-445	14.5
Viscosity Index	ASTM D-2270	130
Flash Point (COC) °C	ASTM D-92	236
Pour Point °C	ASTM D-97	-27

Petromax Grease and Lubricants Industries (FZE)

ISO 14001:2015 & ISO 9001:2015 CERTIFIED BLENDING PLANT

P.O. Box:120551, SAIF Zone – Sharjah, United Arab Emirates. Tel: +971 6 5551766

ibrahim@petromaxgli.com | www.petromaxgli.com