

FASTOL MULTIGRADE ENGINE OIL API CF-4/SG SAE 15W-40 & 20W-50

DESCRIPTION:

FASTOL API CF-4/SG is a heavy duty multi-functional diesel engine oil specifically formulated with a blend of refined base oils and specially selected additives to provide excellent performance in all recommended applications. **FASTOL API CF-4/SG** is designed to lubricate diesel engine requiring CF-4 or SG performance lubricants operating under severe service condition.

APPLICATIONS:

Recommended for use in naturally aspirated, high speed turbo charged or super charged diesel and gasoline engines, in on-highway, off-highway, construction, sports utility vehicles, pickup and delivery and passenger car, vans service, generators, marine diesel engines requiring API CF-4/SG fluid.

BENEFITS:

- ✓ Unmatched varnish, sludge and carbon deposit control.
- ✓ Longer drain intervals and lowers maintenance cost.
- ✓ Increases fuel efficiency and less engine wear.
- ✓ Neutralizes corrosive acid and possesses excellent shear stability for stay-in-grade viscosity performance.
- ✓ Good oxidation stability.

TYPICAL DATA			
Product	FASTOL MULTIGRADE ENGINE OIL		
SAE Rating	SAE 15W-40 & 20W-50		
API Level	CF-4/SG		
Physical Characteristics	Test Method	Typical Value	
SAE Rating		15W-40	20W-50
Kinematic Viscosity @ 100 °C (cst)	ASTM D-445	14.50	18.50
Viscosity Index	ASTM D-2270	130	125
Flash Point (COC) °C	ASTM D-92	234	236
Pour Point °C	ASTM D-97	-21	-18
TBN, mg KOH/g	ASTM D- 2896	9.0	9.0