

## SYNTHYDE TRIBOLOGY GX7

### API SL/CF SAE 10W-40

**DESCRIPTION:**

**SYNTHYDE TRIBOLOGY GX7** is a synthetic blend gasoline engine lubricant formulated with specially designed additive package and highly refined base oils for naturally aspirated or turbo charge vehicles requiring API SL performance lubricants.

**APPLICATIONS:**

**SYNTHYDE TRIBOLOGY GX7** is recommended for naturally aspirated, turbocharged gasoline engines. Also suitable for Passenger cars, Vans, Light commercial vehicles engines required API **SL** or **CF** performance. It is equally suitable for engine converted to **CNG** or **LPG**. **SYNTHYDE TRIBOLOGY GX7** is also capable of meeting API specification SL, SJ, SG, and API SF

**BENEFITS:**

- Deliver excellent performance at high Ambient temperature
- Provides more protection against black sludge formation, wear and corrosion
- Prolongs engine life
- Having high shared stability and anti-oxidant characteristics

TYPICAL DATA		
Product	SYNTHYDE TRIBOLOGY GX7	
SAE Rating	SAE 10w-40	
API Level	SL/ CF	
<b>Physical Characteristics</b>	<b>Test Method</b>	<b>Typical Value</b>
SAE Rating		<b>10W-40</b>
Kinematic Viscosity @ 100 °C (cst)	ASTM D-445	14.5
Viscosity Index	ASTM D-2270	125
Flash Point (COC) °C	ASTM D-92	236
Pour Point °C	ASTM D-97	-27