



Gear Oil API GL-4

Description:

FASTOL GEAR OIL API GL-4 is a high performance, multipurpose extreme pressure Gear Oil blended from selected Sulphur & Phosphorus additives to meet API service classification of GL-4.

Application:

FASTOL GEAR OIL API GL-4 is recommended for mechanical transmission of all type of mechanical Cars, Commercial Vehicles. **FASTOL GEAR OIL API GL-4** is suitable for the lubrication of hypoid gear wheels or spiral bevel in transmission, axel and steering box of vehicles operating under moderate service conditions.

Benefits:

- ✓ Excellent shear stability and gear performance.
- ✓ Superior protection against wear.
- ✓ Excellent protection against rust and corrosion.
- ✓ Compatible with other gear lubricants.
- ✓ Better oxidation and thermal stability.
- ✓ Remarkable load carrying ability.
- ✓ Robust manual transmission performance.

Typical Data			
Product	FASTOL GEAR OIL		
SAE Rating	90 and 140		
API Performance	GL-4		
Physical Characteristics			
Test	Test Method	Typical Value	
SAE Rating		90	140
Kinematic Viscosity (cst)@100 °C	ASTM D- 445	15.5	29
Viscosity Index	ASTM D- 2270	97	97
Flash Point COC, °C	ASTM D- 92	230	230
Pour Point	ASTM D-97	-12	-12