

SYNTHYDE TRIBOLOGY GX9

API SN/CF SAE 5W-30

DESCRIPTION:

SYNTHYDE TRIBOLOGY GX9 is an advance carefully balanced synthetic blend gasoline engine lubricant formulated with specially designed additive package and highly refined base oils for naturally aspirated or turbo charge vehicles requiring API SN performance lubricants.

APPLICATIONS:

SYNTHYDE TRIBOLOGY GX9 is recommended for naturally aspirated, turbocharged gasoline engines. Also suitable for Passenger cars, Vans, Light commercial vehicles engines where API **SN** or **CF** performance is recommended. It is equally suitable for engine converted to **CNG** or **LPG**. **SYNTHYDE TRIBOLOGY GX9** is also capable of meeting API specification **SL, SJ, SG, SF** and **API CF**

BENEFITS:

- Excellent resistibility to high temperature degradation
- Superior protection against varnish, corrosion, and sludge formation
- Prolongs engine life
- Stay in grade characteristics at high temperature
- Having effective shared stability and antioxidant characteristics

TYPICAL DATA		
Product	SYNTHYDE TRIBOLOGY GX9	
SAE Rating	SAE 5w-30	
API Level	SN/ CF	
Physical Characteristics	Test Method	Typical Value
SAE Rating		5W-30
Kinematic Viscosity @ 100 °C (cst)	ASTM D-445	10.5
Viscosity Index	ASTM D-2270	130
Flash Point (COC) °C	ASTM D-92	236
Pour Point °C	ASTM D-97	-30